

BRIGHT CYLINDER

PIXEL PITCH (mm)	2.8 x 5.6	3.9 x 7.8	5.4 x 10.4	7.8 x 7.8	10.4 x 10.4
BRIGHTNESS (cd/m²)	800 - 5500	800 - 5500	800 - 5500	800 - 5500	800 - 8000
CABINET SIZE W X H (mm)	1000 x 500	1000 x 500	1000 x 500	1000 x 500	1000 x 500
MIN. DIAMETER (mm)	636	636	636	636	636
CABINET RESOLUTION (px)	352 x 88	256 x 64	192 x 48	128 x 64	96 x 48
WEIGHT (kg/m²)	~8	~8	~8	~8	~8
MAX./AV. POWER CONSUMPTION (W/m²)	800 / 240	800 / 240	800 / 240	800 / 240	800 / 240
LIFETIME (h)	≥100 000	≥100 000	≥100 000	≥100 000	≥100 000
REFRESH RATE (Hz)	1920 / 3840	1920 / 3840	1920 / 3840	1920 / 3840	1920 / 3840
MIN. VIEWING DISTANCE (m)	6	8	10	8	10
VIEWING ANGLE (°)	160 / 160	160 / 160	160 / 160	160 / 160	160 / 160
GRAY SCALE (bit)	14	14	14	14	14
OPERATION TEMPERATURE (°C) / HUMIDITY (%)	-10~40 / 90	-10~40 / 90	-10~40 / 90	-10~40 / 90	-10~40 / 90
IP RATING	IP22	IP22	IP22	IP22	IP22
TRANSPARENCY (%)	45	65	75	65	75
APPLICATION	INDOOR	INDOOR	INDOOR	INDOOR	INDOOR