

BRIGHT LIGHT OUTDOOR

PIXEL PITCH (mm)	3.9 x 7.8	5.2 x 10.4	7.8 x 7.8	10.4 x 10.4
BRIGHTNESS (cd/m ²)	800 - 5500	800 - 5500	800 - 5500	800 - 5500
CABINET SIZE W X H (mm)	1000 x 500	1000 x 500	1000 x 500	1000 x 500
CABINET RESOLUTION (px)	256 x 64	192 x 48	128 x 64	96 x 48
WEIGHT (kg/m ²)	~15	~15	~15	~15
MAX./AV POWER CONSUMPTION (W/m ²)	800 / 240	800 / 240	800 / 240	800 / 240
LIFETIME (h)	≥100 000	≥100 000	≥100 000	≥100 000
REFRESH RATE (Hz)	1920 / 3840	1920 / 3840	1920 / 3840	1920 / 3840
MIN. VIEWING DISTANCE (m)	8	10	8	10
VIEWING ANGLE (°)	160 / 160	160 / 160	160 / 160	160 / 160
GRAY SCALE (bit)	14	14	14	14
OPERATION TEMPERATURE (°C) / HUMIDITY (%)	-40~45	-40~45	-40~45	-40~45
IP RATING	IP65	IP65	IP65	IP65
TRANSPARENCY (%)	30	35	40	45
MAINTENANCE	przód / tył	przód / tył	przód / tył	przód / tył
APPLICATION	OUTDOOR	OUTDOOR	OUTDOOR	OUTDOOR