

LIGHT RENTAL

| PIXEL PITCH (mm) | 2.8 x 5.6 | 3.9 x 7.8 | 5.2 x 10.4 | 7.8 x 7.8 | 10.4 x 10.4 |
|---|-------------------|-------------------|-------------------|-------------------|-------------------|
| BRIGHTNESS (cd/m²) | 500 - 8000 | 500 - 8000 | 500 - 8000 | 500 - 8000 | 500 - 8000 |
| CABINET SIZE W x H (mm) | 1000 x 500 / 1000 | 1000 x 500 / 1000 | 1000 x 500 / 1000 | 1000 x 500 / 1000 | 1000 x 500 / 1000 |
| CABINET RESOLUTION (px) | 352 x 88 | 256 x 64 | 192 x 48 | 128 x 64 | 96 x 48 |
| WEIGHT (kg/m²) | ~9 | ~9 | ~9 | ~9 | ~9 |
| MAX./AV. POWER CONSUMPTION (W/m²) | 800 / 240 | 800 / 240 | 800 / 240 | 800 / 240 | 800 / 240 |
| LIFETIME (h) | ≥100 000 | ≥100 000 | ≥100 000 | ≥100 000 | ≥100 000 |
| REFRESH RATE (Hz) | 1920 / 3840 | 1920 / 3840 | 1920 / 3840 | 1920 / 3840 | 1920 / 3840 |
| MIN. VIEWING DISTANCE (m) | 6 | 8 | 10 | 8 | 10 |
| VIEWING ANGLE (°) | 160 / 160 | 160 / 160 | 160 / 160 | 160 / 160 | 160 / 160 |
| GRAY SCALE (bit) | 14 | 14 | 14 | 14 | 14 |
| OPERATION TEMPERATURE (°C) / HUMIDITY (%) | -10~40 / 90 | -10~40 / 90 | -10~40 / 90 | -10~40 / 90 | -10~40 / 90 |
| IP RATING | IP22 | IP22 | IP22 | IP22 | IP22 |
| TRANSPARENCY (%) | 45 | 65 | 75 | 65 | 75 |
| MAINTENANCE | przód / tył | przód / tył | przód / tył | przód / tył | przód / tył |
| APPLICATION | INDOOR | INDOOR | INDOOR | INDOOR | INDOOR |